

20-60
Watt



SELV



PF
 $\lambda \geq 0,95$

IP20

CE

EMC




M

M

F



$t_a -10^{\circ} \div +40^{\circ}C$



| Part Number | I _{out} | V _{out} Led Min | V _{out} Led Max | W Max | Dimensions A x B x C |
|--------------|------------------|--------------------------|--------------------------|-------|----------------------|
| A40CCBXL600B | 250÷750mA | 30V | 85V | 60W | 125 x 74 x 35 |
| A40CCBXH600B | 800÷1500mA | 10V | 48V | 60W | 125 x 74 x 35 |

CCBXL60


| I _o | V _o (min) | V _o (max) | P _o (max) |
|----------------|----------------------|----------------------|----------------------|
| 250mA | 50V | 80V | 20W |
| 350mA | 45V | 85V | 30W |
| 450mA | 35V | 85V | 38W |
| 500mA | 35V | 85V | 42W |
| 550mA | 30V | 85V | 46W |
| 600mA | 30V | 85V | 51W |
| 700mA | 30V | 85V | 59W |
| 750mA | 30V | 80V | 60W |

CCBXH60

| I _o | V _o (min) | V _o (max) | P _o (max) |
|----------------|----------------------|----------------------|----------------------|
| 800mA | 25V | 47V | 37W |
| 900mA | 20V | 48V | 43W |
| 1000mA | 18V | 48V | 48W |
| 1100mA | 18V | 48V | 52W |
| 1200mA | 12V | 48V | 57W |
| 1300mA | 10V | 46V | 60W |
| 1400mA | 10V | 42V | 60W |
| 1500mA | 10V | 40V | 60W |



Datasheet download



Alimentatore LED Multicurrent

- Alimentatore indipendente - IP20 - Classe II di isolamento - SELV
- Uscita in corrente costante regolabile con Dip-Switches:
A40CCBXL600B: da 250 a 750mA, $\pm 5\%$
A40CCBXH600B: da 800 a 1500mA, $\pm 5\%$,
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Morsetti rapidi
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione: 200V ÷ 240V/AC - Uscita stabilizzata

Multicurrent LED Driver

- For independent mounting - IP20 - Insulation class II - SELV
- Output in constant current settable by DIP-Switches:
A40CCBXL600B: from 250 to 750mA, $\pm 5\%$
A40CCBXH600B: from 800 to 1500mA, $\pm 5\%$,
- Self-resetting protection against overtemperatures, open circuit and against output short circuits
- Fast terminals
- Cable clamp for flat and round cables
- Input voltage: 200V ÷ 240V/AC - Steady output