


Dimmable LED drivers – PBT Dimmable – TRIAC/IGBT/Mosfet

Constant voltage dimmable LED driver / Alimentatore dimmerabile per LED a tensione costante

Made in Italy 



Part number Codice prodotto	P out W @230V	V out DC ±5%	I out DC max @230V	λ Power Factor	Efficiency in full-load @230V	tc °C
A40PBT10000B	100	24	4,16 A	0,98	89%	75
A40PBT15000B	150	24	6,25 A	0,98	91%	75
A40PBT20000B	200	24	8,33 A	0,98	93%	80

Features

- IP20 independent LED driver (indoor use)
- Supplied with terminal cover and cable retainer
- Class II protection against electric shock for direct or indirect contact

Caratteristiche

- Alimentatore LED indipendente IP20 (uso interno)
- Fornito di coprimorsetto e serracavo
- Protezione in classe II contro le scosse elettriche per contatti diretti e indiretti

Directives / Direttive:

2014/35/EU (LVD); 2014/30/EU (EMC); RoHs 2011/65/EU + 2015/863/EU (RoHs); 2009/125/ECODESIGN regulation (EU) n°2019/2020 and 341/2021 amendment

Standards compliance: Conformità alle norme:

EN 61347-2-13:2014 + A1:2017; EN 61347-1:2015; EN 61347-1:2015 + A1:2021
EN IEC 62384:2020
EN 55015:2019 + A11:2020; EN 61000-3-3:2013; EN 61457:2009;
EN IEC 61000-3-2:2019 + A1:2021
EN 63000:2018
EN IEC 62442-3:2022



Dimmable LED drivers – PBT Dimmable – TRIAC/IGBT/Mosfet

Constant voltage dimmable LED driver / Alimentatore dimmerabile per LED a tensione costante

Made in Italy 


Other electrical data	
Nominal input voltage AC	220-240 V
Mains frequency	50/60 Hz
iTHD	6 %
Inrush current	15 A, 130 μ s
Surge capability (L-N)	> 1 kV
Nominal output voltage DC	24 V \pm 5%
Output PWM frequency	1 kHz
Minimum output load	10 W (PBT100), 30W (PBT150), 50W (PBT200)
Output voltage ripple (100 Hz)	< 5%
No-load proof	YES
Intended for no-load operation	NO
Output PstLM (Flicker value)	\leq 1
Output SVM (Stroboscopic effects value)	\leq 0,4
Insulation primary/secondary:	Class II SELV 3750V AC
Leakage current:	< 0,5 mA
Temperatures and operating conditions	
Ambient temperature range	-10...+40 °C
Storage temperature range	-15...+50 °C
Capabilities	
Dimmable	YES
Dimming interface	TRIAC, IGBT, MOSFET
Protections	Open load, short-circuit, overload, overtemperature
Connections	
Cables cross-section (input side)	0,5-2,5 mm ² , 13-20 AWG
Wire preparation lenght (input side)	4...7 mm
Cables cross-section (output side)	0,5-2,5 mm ² , 13-20 AWG
Wire preparation lenght (output side)	4...7 mm
Connections	0,5-2,5 mm ² screw or fast connectors
Nominal life-time	50000h @Ta 40 °C

Dimmable LED drivers – PBT Dimmable – TRIAC/IGBT/Mosfet

Constant voltage dimmable LED driver / Alimentatore dimmerabile per LED a tensione costante

Made in Italy 

Product dimensions



Color & materials

Casing material:	Polycarbonate V0
Color	White

Product weight

A40PBT10000B	320 gr.
A40PBT15000B	320 gr.
A40PBT20000B	320 gr.