



Part Number	Iout	Vout Led Min	Vout Led Max@230V	Vout Led max @110V	Uout	W @230V	W @110V	Dimensions A x B x c
A40FLAT112WB	350mA	2,75	40	31	45V	14W	11W	126 x 47 x 16,5
A40FLAT306WB	700mA	2,75	21*	14*	24V	14W	10W	126 x 47 x 16,5
A40FLAT1200B	1,2Amax	-	-	-	12V	14W	11W	126 x 47 x 16,5
A40FLAT3000B	1,25Amax	-	-	-	24V	30W	15W	126 x 47 x 16,5

* in CC mode



Datasheet download

Alimentatore per LED di potenza

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Uscita in corrente costante: 350mA, 700mA, +/- 5%
- Uscita a tensione costante 12÷24V/DC
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Basso spessore
- Alimentazione : 110÷240V/AC- Uscita stabilizzata

Driver for High Brightness LEDs

- Independent driver - IP20 - Insulation class II
- Output in constant current: 350mA, 700mA, +/- 5%
- Output in constant tension 12÷24V/DC
- Self-resetting protection against overtemperatures, against open circuit and against output short circuits
- Reduced thickness
- Input voltage: 110÷240V/AC- Steady output.

