

75÷200
WattPF
 $\lambda \geq 0,98$

IP 20



EMC




SELV



80 mm

 $t_a -10^{\circ} \div +40^{\circ}C$ 

On request



Part Number	Output V	Ouput I _{max} @ 230V	Ouput I _{max} @ 110V	W @230V	W @110V	Dimensions A x B x c	
A40PBOX0750B	12V	6,25A	5A	75W	60W	210 x 75 x 35	
A40PBOX1000B	12V	8,33A	5A	100W	60W	210 x 75 x 35	
A40PBX10000B	24V	4,16A	2,5A	100W	60W	210 x 75 x 35	•
A40PBX15000B	24V	6,25A	2,5A	150W	60W	210 x 75 x 35	•
A40PBX20000B	24V	8,33A	3,75A	200W	90W	210 x 75 x 35	



Datasheet download

Alimentatore per LED di potenza

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Uscita in tensione costante, $\pm 5\%$
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario
- Rifasatore attivo, costruzione compatta e basso riscaldamento.
- Doppio collegamento di uscita
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione: 110÷240V/AC - Uscita stabilizzata. A richiesta, alimentazione a 230VDC

Driver for High Brightness LEDs

- For independent use - IP20 - Insulation class II
- Steady voltage output, $\pm 5\%$
- Self-resetting protection against overtemperatures, against open circuit and against output short circuits
- Active power factor correction, compact size and reduced heating.
- Double output.
- Cable clamp for flat and round cables
- Input voltage: 110÷240V/AC - Steady output. On request, 230VDC input voltage