

60
Watt



PF
 $\lambda \geq 0,96$

IP 65

SELV




EMC



110

$t_a -10^{\circ} \div +45^{\circ}C$



| Part Number | Output V | Output I _{max} | W | Dimensions A x B x C | Protocol |
|--------------|----------|-------------------------|-----|----------------------|-----------------------|
| A40PLE06000B | 24V/DC | 2,5A | 60W | 175 x 50 x 31 | TRIAC / IGBT / MOSFET |



Datasheet download

Alimentatore dimmerabile per moduli LED

- Alimentatore indipendente da incorporare - IP65 - Classe II di isolamento
- Regolazione della luce a taglio di fase con dimmer TRIAC, IGBT e MOSFET con minimo regolabile, compatibili con carichi LED
- Uscita in tensione costante 24VDC, +/-5%
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Alimentazione: 230V/AC +/- 10% - Uscita stabilizzata.

Dimmable driver for LED modules

- For independent use to be built in - IP65 - Insulation class II
- Light regulation by TRIAC, IGBT and MOSFET dimmers with settable minimum, compatible with LED loads
- Output in steady voltage 24VDC, +/-5%
- Self-resetting protection against overtemperatures against open circuit and against output short circuits.
- Input voltage: 230V/AC +/- 10% - Steady output.