



Comando DALI DT8 o Push (settaggio a 500mA)
DALI DT8 or Push control (set at 500mA)

Part Number	CCT (K)	Lumen Typ. 2700K	Lumen Typ. 6500K	Beam	I (max)	V (Typ)	W	Ø	Standard Size	EEC**
A40SPEVTW0W0	2700K+6500K	770	900	Wide 40°	500mA	18V	9W	50 mm	MR16	F

** The EEC specification refers in each case to the instalLED light source(s)

Comando DMX o piena potenza su entrambi i canali (settaggio a 250mA)
DMX or full power output on both channels (set at 250mA)

Part Number	CCT (K)	Lumen Typ. 2700K	Lumen Typ. 6500K	Beam	I (max)	V (Typ)	W	Ø	Standard Size	EEC**
A40SPEVTW0W0	2700K+6500K	350	450	Wide 40°	250mA	18V	9W	50 mm	MR16	F

** The EEC specification refers in each case to the instalLED light source(s)



Datasheet download

Spot a LED di potenza Bianco Dinamico MR16

- Alimentazione in corrente costante 500mA (DALI/PUSH) o 250mA (DMX)
- Utilizzare alimentatori DALI DT8 o pulsante con bilanciamento dei canali
- Disponibile con riflettore wide 40°
- Si adatta in sedi per lampadina MR16 con retro aperto
- CRI 90, R9>50
- Bianco dinamico da 2700 a 6500K

High Brightness LED spot - MR16

- Powered in constant current 500mA (DALI/PUSH) or 250mA (DMX)
- To be used with DALI DT8 drivers or push-button with channel balancing.
- Available with wide 40°
- Suitable for being built in standard MR16 applications with open back.
- CRI 90, R9>50
- Tunable white from 2700K to 6500K